

JBL Cooler 100

Cooling fan for fresh- and saltwater aquariums

Suitable for: < 🖈 🏏 🗞 🐋



- Cooling of the water temperature by 2 4 °C: cooling blower with ventilators for aquariums
- Easy to install on the aquarium rim: thickness max. 2.5 cm. Switch on by means of toggle switch on the casing
- Water cooling by air flow at the water surface, evaporation of the warm water. Expandable with BL CoolControl
- Safety: 12 V small voltage, safety cover grid. Universal power supply for all common mains voltages worldwide
- Package contents: cooling fan for aquariums, Cooler



You may also be interested in γ

You can find a complete overview here: https://www.jbl.de/qr/60440



JBL PROTEMP S 25 Safety heater-stat with protective basket



JBL PROTEMP S 50 Safety heater-stat with protective basket



JBL PROTEMP S 100 Safety heater-stat with protective basket



JBL PROTEMP \$ 150 Safety heater-stat with protective basket













JBL adapter UK for all flat-pin plugs





JBL Cooler 100 Product information

Temperature control

There are two important factors which affect the water temperature in the aquarium: firstly the room temperature and secondly direct sunlight. If the room temperature in summer increases significantly, it is important to check the temperature in the aquarium regularly. It should be 24-26 °C. Temperatures above 30 °C are a problem and can cause substantial damage to fish and plants. Furthermore aquariums should never be exposed to direct sunlight. The higher the temperature, the less effectively the oxygen, which is vital for the animals, dissolves.

Easy to install

The bracket of the cooling fan is placed onto the aquarium rim (up to max. 2.5 cm thickness) and fixed with clamp screws.

Cooling by evaporation

The JBL cooler for freshwater and saltwater cools down by 2-4 °C with the help of 2 fans. The fan makes the warm water evaporate at the water surface and thus generates cold. Comparable to evaporation cooling of a wet body part which is exposed to the wind.

Safety

The water cooler has a safety cover grid and is operated with a low voltage of 12 V.

| Further information | |
|-----------------------|---|
| FAQ | ~ |
| Blog | ~ |
| Press | ~ |
| Laboratory/calculator | × |
| Worth reading | ✓ |
| Spare parts | ✓ |
| Video | ✓ |
| GarantiePlus | × |
| Instructions | ✓ |
| QR code | |







JBL Cooler 100

| Food type | |
|------------------|--|
| Sub product type | |
| Dosing | |

