



Cooling blower for freshwater and marine aquariums









- Cooling of the water temperature by 2 4 °C at increased ambient temperature: cooling blower with ventilators for aquariums
- Easy to install on the aquarium rim: thickness max. 2.5 cm. Switch on by means of toggle switch on the casing
- Water cooling by air flow at the water surface, evaporation of the warm water. Expandable with temperature control JBL CoolControl
- Safety: 12 V low voltage, safety cover grid. Universal power supply for all common mains voltages worldwide
- Package contents: cooling blower for aquariums, cooler



You may also be interested in

You can find a complete overview here: https://www.jbl.de/qr/60442





JBL PROTEMP S 25 Safety heater-stat with protective basket



JBL PROTEMP S 50 Safety heater-stat with protective basket



JBL PROTEMP S 100 Safety heater-stat with protective basket



JBL PROTEMP S 150 Safety heater-stat with protective basket



Date: 01.01.2024 Produced by:

Country: Norway Language: English









JBL adapter UK for all flat-pin plugs









Product information

Temperature control

There are two important factors which affect the water temperature in the aquarium: firstly the room temperature and secondly direct sunlight. If the room temperature in summer increases significantly, it is important to check the temperature in the aquarium regularly. It should be 24-26 °C. Temperatures above 30 °C are a problem and can cause substantial damage to fish and plants. Furthermore aquariums should never be exposed to direct sunlight. The higher the temperature, the less effectively the oxygen, which is vital for the animals, dissolves.

Easy to install

The bracket of the cooling blower is placed onto the aquarium rim (up to max. 2.5 cm thickness) and fixed with clamp screws.

Cooling by evaporation The JBL coolers for freshwater and marine aquariums cool by 2-4 °C with the help of fans. The fans make the warm water evaporate at the water surface and thus generate cold. Comparable to evaporation cooling of a wet body part which is exposed to the wind.

The water cooler has a safety cover grid and is operated with a low voltage of 12 V.

Further information	
FAQ	~
Blog	~
Press	~
Laboratory/calculator	×
Worth reading	~
Spare parts	~
Video	~
GarantiePlus	×
Instructions	~
QR code	







Food type	-
Sub product type	-
Dosing	-

