




JBL PROFLORA CO2 REGULATOR PROFESSIONAL

Pressure regulator with 2 displays & valve for CO2

Suitable for: 



- The pressure reducer reduces the cylinder pressure from approx. 60 bar (displayed on pressure gauge 1) to a low 1.2 bar working pressure (displayed on pressure gauge 2), so that the CO2 supply can be easily regulated
- Screw the pressure reducer onto the CO2 pressurised gas cylinder, connect the solenoid valve to the timer (not included) or CO2 control unit (not included) and regulate the amount of CO2 added using the fine needle valve
- The pressure reducer fits disposable CO2 cylinders (U system) and refillable cylinders (M system). By unscrewing the knurled nut (W21.8x1/14) with an Allen key, the pressure reducer fits the M10x1 thread of the disposable cylinders
- Very high-quality design: anodised aluminium, precisely CNC-milled in titanium colour, low-noise solenoid valve. Reliable sealing washer instead of O-ring
- Package contents: 1 CO2 pressure reducer with 2 pressure gauges (for working & cylinder pressure) for disposable and refillable cylinders, solenoid valve and unscrewable adapter - then suitable for disposable CO2 cylinders





JBL PROFLORA CO2 REGULATOR PROFESSIONAL

Spare parts



**JBL PROFLORA CO2 O-
ring for m**



**JBL PF CO2 flat gasket
for u**



**JBL PF CO2 O-ring for
VALVE**



**JBL PF CO2 CONTROL
cable for VALVE**



**JBL PF CO2 CONTROL
power supply unit 12V**





JBL PROFLORA CO2 REGULATOR PROFESSIONAL



Product information

Easy to install


Screw the fitting onto the refillable or disposable CO2 cylinder. Use a hose to connect the hose connection from the permanently connected solenoid valve to a bubble counter/check valve and then to the diffuser/reactor in the aquarium. Adjust the number of CO2 bubbles on the fine needle valve. The CO2 permanent test provides feedback as to whether the amount of CO2 added is correct.

Night switch-off/CO2 control:

The solenoid valve can either be switched on and off by a timer (not included) so that it switches on the light and the CO2 in the morning (and switches off again in the evening) or the solenoid valve is switched on and off by a CO2 control unit (JBL PROFLORA CO2 CONTROL) to regulate the CO2 supply and thus the pH value automatically.

Tip: Can be easily converted to a disposable cylinder system by unscrewing the knurled union nut with an Allen key.

Function of the pressure reducer (= pressure regulator): To reduce the pressure from the pressurised gas cylinder, a pressure reducer is screwed on. It reduces the 50-60 bar cylinder pressure to a working pressure of approx. 1.2 bar. These 1.2 bar are then dosed by a small handwheel (fine needle valve) so precisely that individual CO2 bubbles can be seen and counted in the bubble counter connected. The cylinder pressure and the working pressure are indicated on pressure gauges on this pressure reducer. These displays are not strictly necessary, as - unlike with diving cylinders with compressed air - the cylinder pressure does not slowly drop, and you do not need to be warned when the cylinder is running low. Instead, the pressure remains at its maximum pressure and then drops to zero in a very short time. So, unfortunately, there is no slow decrease of the cylinder filling pressure. The working pressure would only be important if it needed to be adjusted, though this is normally not necessary.

| Further information | |
|-----------------------|---|
| FAQ | ✓ |
| Blog | ✓ |
| Press | ✓ |
| Laboratory/calculator | ✗ |
| Worth reading | ✓ |
| Spare parts | ✓ |
| Video | ✓ |
| GarantiePlus | ✓ |
| Instructions | ✓ |
| QR code |  |





JBL PROFLORA CO2 REGULATOR PROFESSIONAL

Product details

| Article data | |
|--------------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| EAN number | 4014162646729 |
| EAN as barcode | |
| For Ø | 4/6 mm |
| - | - |
| Expiry months | - |
| RRP incl. VAT | 200,13 € |
| Base price | - |
| Nominal filling quantity | - |
| Base quantity | 1 |
| Gross weight | 782 g |
| Net weight | 655 g |
| Weight change | - |

| Disposal | |
|-------------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| Green dot | ✓ |
| Group electronic waste | Small appliances that can be used in private households |
| Disposal weight | 478 g |
| Battery type | - |
| Battery return | - |
| Battery rechargeable | - |
| Disposal weight battery | - |
| Non-returnable glass | - |
| PPK | 127 g |
| Plastic small | - |
| Plastic large | - |
| Disposal weight metal | 0 g |

| Features | |
|--------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |





| Features | |
|----------------------|---|
| Animal species | Arowana, Axolotl, Barbels, Bettas, Bichirs/reedfish, Blowfish, Catfish, Cichlids (South America), Crayfish, Danions, Discus, Dwarf shrimps, Flowerhorn, Goldfish, Gouramis, Guppy, Juvenile fish, Killifish, Livebearers, Loaches, Panchaxes, Rainbowfish, Snails, Spiny eels, Tetra, Veiltails, freshwater butterflyfish |
| Animal size | For all animal sizes |
| Animal age group | All aquarium fish |
| Volume of habitat | For all aquariums |
| Material | Metal (aluminium), plastic (ABS), metal (stainless steel), metal (copper) |
| Food type | - |
| Colour | silver / black |
| Dosage | - |
| Transport conditions | - |



JBL PROFLORA CO2 REGULATOR PROFESSIONAL

| Electronic label / illuminant | |
|-------------------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| Ambient temperature | - |
| Start time | - |
| Mercury | - |
| Tube length | - |
| Service life | - |
| Lumen | - |
| CRI value | - |
| Dimmable | - |
| Switching cycles | - |
| PAR value | - |
| Energy efficiency class | - |
| UV-A | - |
| UV-B | - |
| UV-C | - |
| Colour temperature | - |
| Base designation | - |

| Technical data | |
|-------------------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| Range in litres | - |
| Range from - to | - |
| Range in days | - |
| Range tank length | - |
| Output in watts | - |
| Output per hour | - |
| Output per day | - |
| Height | 90 mm |
| Length | 80 mm |
| Width | 140 mm |
| Diameter | - |
| Voltage | - |
| For | - |
| T8 26mm (watt) | - |
| T5 16mm (watt) | - |
| Size | - |
| Content for | - |
| Filter container volume | - |
| Volume filter media | - |
| Hose connections pressure/out | - |





| Technical data | |
|-----------------------------|---|
| Hose connections suction/in | - |
| Delivery head | - |





JBL PROFLORA CO2 REGULATOR PROFESSIONAL

| | |
|------------------|---|
| Food type | - |
| Sub product type | - |
| Dosing | - |





Additional information for the specialist trade sector

| Article data | |
|----------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| VAT | 19% |
| Sales unit (SU) | 1 |
| Volume packaging | 1.93l |
| Dimensions (l/w/h) | 105 mm/121 mm/152 mm |
| Layer | 66 |
| Pallet | 528 |
| Category of products | 3 |
| Customs tariff | 84811099 |
| Country of origin | IT |
| Type of packaging | Faltschachtel/Karton |

| PU 1 data | |
|------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| PU 1 material | None |
| PU 1 weight | - |
| PU 1 length | - |
| PU 1 width/depth | - |
| PU 1 height | - |

| PU 2 data | |
|------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| PU 2 material | None |
| PU 2 weight | - |
| PU 2 length | - |
| PU 2 width/depth | - |
| PU 2 height | - |

| Trade data | |
|-------------------|---|
| Product name | JBL PROFLORA CO2 REGULATOR PROFESSIONAL |
| Art. No. | 6467200 |
| Till receipt text | CO2 REGUL PROF |
| Shelf placement | - |

